MARSTEK

Power Anywhere & Anytime

SMART METER CT003

- Anti Feed-in with Real-Time Monitoring
- Better Compatibility with MARSTEK Products
- Integrated with Household Smart Meters
- Support Bluetooth/WIFI/Ethernet Connections
- High Security and Strong Signal Strength





Marstek Energy Co., Limited

Add: BLDG#A, Changfang Industrial Park, No.2 Guihua 5th Road, Pingshan District, Shenzhen, Guangdong, China

Tel: 86-755-28398778 Email: market@marstekenergy.com Web: www.marstekenergy.com

SPECIFICATIONS



SMR-P1



SMR-TIC



SMR-IR

Model	SMR-P1	SMR-TIC	SMR-IR
Power Supply Parameters			
AC Voltage	/	/	/
DC Voltage	5V / 1A (Type-C)	5V / 1A (Type-C)	5V / 1A (Type-C)
Connectivity			
WIFI	2.4 GHz : n20	2.4 GHz : n20	2.4 GHz : n20
Bluetooth Version	BT 5.4	BT 5.4	BT 5.4
Modulation Mode	GFSK	GFSK	GFSK
Electric Meter Port	P1	TIC	IR
Communication Ports	WIFI	WIFI / Ethernet	WIFI / Ethernet
Basic Parameters			
Operating Temperature	-20°C ~ 45°C	-20°C ~ 45°C	-20°C ~ 45°C
Device Power Consumption	<2W	<2W	<2W
Dimensions	43.7 × 43.7 × 14mm	49.5 × 30 × 31mm	57 × 57 × 34mm
Weight	18.6g	26.7g	38.1g